



ELADOS® EMP-KKS


Diaphragm Piston Metering Pump

- ▲ High metering accuracy with degassing products
- ▲ Metering with smallest possible rate capability
- ▲ High operating safety by permanent self-venting



ELADOS® EMP-KKS:

- ▲ Multifunction electronics
- ▲ Flexible pulse & standard signal processing
- ▲ Optional available:
 - integrated pH or redox controller



Pump capacity [l/h]	0 - 0,2	0 - 0,5	0 - 0,9	0 - 1,4								
Metering back pressure max. [kPa]	1000 (10 bar)											
Number of strokes [1/min.]	122											
Metering volume/stroke max. [ml]	0,027	0,068	0,12	0,19								
Electrical version	<p>E 10 On/off switch, mechanical stroke adjustment E 60 On/off switch, mechanical stroke adjustment</p> <ul style="list-style-type: none"> • back-lit graphic display, 4 operating keys • Single stroke control (each stroke is completely executed) • Metering monitoring via stroke-signal output or via external metering-monitoring system (e.g. oval gear meter) possible • Registration of operating and consumption data • Diaphragm failure detection <p>Selectable operating modes:</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Internal mode</th> <th>External mode</th> </tr> </thead> <tbody> <tr> <td> Selection of metering rate/ metering frequency via: <ul style="list-style-type: none"> • Strokes/min • Percent • Liter/h (or gallon/h) </td> <td> <ul style="list-style-type: none"> • Pulse mode (actuation via pulses) <ul style="list-style-type: none"> - Pulse multiplication (one incoming pulse = n metering strokes) - Pulse division (n incoming pulses = 1 metering stroke) • Standard signal mode (actuation via external standard signal 0/4-20mA or 20-0/4mA) • Charge mode (a previously selected quantity is metered, with initiation via an external initiation pulse) </td> </tr> <tr> <th>Inputs</th> <th>Outputs</th> </tr> <tr> <td> <ul style="list-style-type: none"> • Level monitoring, package vessel (reserve and empty signal) • Pulse • Standard signal • Enable </td> <td> <ul style="list-style-type: none"> • Level monitoring package vessel • Stroke signal • Malfunction </td> </tr> </tbody> </table> <p>E 60^{PLUS} as E 60, but additional display of real metering quantity/time and automatic readjustment of pump output (only in combination with external flow monitoring system, e.g. oval gear meter)</p>				Internal mode	External mode	Selection of metering rate/ metering frequency via: <ul style="list-style-type: none"> • Strokes/min • Percent • Liter/h (or gallon/h) 	<ul style="list-style-type: none"> • Pulse mode (actuation via pulses) <ul style="list-style-type: none"> - Pulse multiplication (one incoming pulse = n metering strokes) - Pulse division (n incoming pulses = 1 metering stroke) • Standard signal mode (actuation via external standard signal 0/4-20mA or 20-0/4mA) • Charge mode (a previously selected quantity is metered, with initiation via an external initiation pulse) 	Inputs	Outputs	<ul style="list-style-type: none"> • Level monitoring, package vessel (reserve and empty signal) • Pulse • Standard signal • Enable 	<ul style="list-style-type: none"> • Level monitoring package vessel • Stroke signal • Malfunction
Internal mode	External mode											
Selection of metering rate/ metering frequency via: <ul style="list-style-type: none"> • Strokes/min • Percent • Liter/h (or gallon/h) 	<ul style="list-style-type: none"> • Pulse mode (actuation via pulses) <ul style="list-style-type: none"> - Pulse multiplication (one incoming pulse = n metering strokes) - Pulse division (n incoming pulses = 1 metering stroke) • Standard signal mode (actuation via external standard signal 0/4-20mA or 20-0/4mA) • Charge mode (a previously selected quantity is metered, with initiation via an external initiation pulse) 											
Inputs	Outputs											
<ul style="list-style-type: none"> • Level monitoring, package vessel (reserve and empty signal) • Pulse • Standard signal • Enable 	<ul style="list-style-type: none"> • Level monitoring package vessel • Stroke signal • Malfunction 											
Power supply	230 V / 50/60 Hz, special versions on request											
Protection class	IP 65											
Pump head material	PVDF											
Sealing material	FPM (Viton B)*, EPDM, FFPM (Kalrez)											
Valve ball material	ceramics											

• Calibration function
• Consumption data acquisition

• Metering readjustment

* Standard



A range of integrated accessories round off the complete programme for all metering applications.